



Multi-band Panel	1710~2170
Vertical Polarization	V
Half-power Beam Width	90°
Fixed Electrical Downtilt	0°

VPol 1710~2170MHz 90° 16dBi 0° Tilt

Electrical specifications	KBT90VP16-1820AT0		
Frequency range (MHz)	1710~1880	1850~1990	1920~2170
Polarization	Vertical		
Gain (dBi)	15.5	15.5	16
Electrical Downtilt (°)	0		
Half-power beam width (°)	Horizontal:90 Vertical:8.5	Horizontal:89 Vertical:8	Horizontal:88 Vertical:7.5
Sidelobe suppression for first sidelobe above main beam (dB)	≥15		
Front-to-back ratio (dB)	≥23		
Impedance (Ω)	50		
VSWR	≤1.4		
Intermodulation IM3 (2×43dBm carrier)	≤-150dBc		
Maximum power (W)	200		
Lighting protection	DC Ground		




Mechanical specifications	
Connector	7/16DIN Female
Connector position	Bottom
Height/width/depth (mm)	1080×160×80
Packing size (mm)	1190×210×150
Weight (kg)	7
Radome material	UPVC
Radome color	Gray
Mechanical tilt (°)	0~15
Operating temperature (°C)	-40~60
Rated wind velocity (m/s)	60
Suitable pole diameter (mm)	50~115
Mounting kit	JM-1800BZ


1710~2170
V

7/16


1710~1880MHz: VPol.



1850~1990MHz: VPol.



1920~2170MHz: VPol.



5Tacche è il marchio di Telecom Italia srl
 080 397 57 86 P.V.A. 06599340723
 www.5tacche.it

MAI PIU' SENZA SEGNALE!